

## Technical Data Sheet **ADITOR® J**

### Grinding aids modifiers of setting time

This products has been specially designed to control the cement setting, accelerating or delaying its initial time. They also have a beneficial effect on the cement hydration, reducing the water demand.

#### Instructions for use and dosage

✦ They can be easily poured on the material to grind (at mill feeding belt) by using a simple pumping system, being recommended to add them out as close to the entrance of the mill as possible.

✦ Recommended dosage: 500-1.000 ppm (g/Tm)

#### Storage

✦ It is recommended to be stored in closed containers, protected from any pollution and cold temperatures, and placed in areas with good ventilation. Avoid high temperatures to prevent any biological contamination in the inside.

✦ Suitable storage materials are stainless steel 316, carbon steel, fibreglass reinforced plastic and other plastic materials.

✦ Maximum time limit to use it: 10-12 months after supply.

#### Handling and transport

✦ Handling these products is not dangerous. Nevertheless, the usual preventive measures for the handling of chemical substances should be adopted.

✦ Disposal of the product or its container should be done complying with the legislation in force, and it is exclusive responsibility of its final user.

✦ Non hazardous product according to the land, sea and air transport regulation.

#### Technical specifications (\*)

Aspect: Dark brown liquid with a faint, characteristic odour

Density(20°C): 1,12 – 1,18 g/cm<sup>3</sup>

(\*) Average values. They are not sales specification



Skin irritation Class 2  
Eye irritation Class 2

**Attention**

(\*) For further information about these additives (current formulation, applications, properties, technical specifications, etc) contact with our Technical Department.